




B.KEOGH & SONS

MANUFACTURING PTY LTD

Vertical Mixers : value adding to grains is an ever increasing trend in rural Australia, and KEOGHS purpose built range of mixers are ideal for blending crushed grains, minerals, medications, liquid supplements and also useful for seed mixing. The HAWK-EQUIP vertical mixer enables fast and easy blending and mixing to your requirements.

B. Keogh & Sons Manufacturing Pty Ltd is Australia's trusted name in commodity handling equipment. For more than 45 years KEOGH'S have been developing and manufacturing grain handling products to meet the needs of rural and commercial producers. In an industry where experience and quality do matter B. Keogh & Sons Manufacturing Pty Ltd is the undisputed leader.



Pictured is a standard HM18015V unit (5.1 m³ or 2.2 tonne unit) with standard Side Auger and Hopper, Site Glass and Liquid Supplement Ring. This picture show the Mixer installed with augers and a Keogh OPTION 4 SCALE SYSTEM. The machine comes fully guarded which are easy to remove and replace. Standard finishes are either painted your choice of the COLORBOND® range, other colors or hot dip galvanized (5.1 m³ and below models only).

The HAWK-EQUIP range of mixers starts at the HM15015V (2.5 m³), through to the impressive HM19535V machine (12.8 m³). All units can be used for grain blending or seed mixing. Standard construction across the entire range

is for 3 mm steel in the cone and walls and 5 mm steel for the lid.

B. Keogh & Sons Manufacturing Pty Ltd – the manufacturers of the trusted and renowned HAWK-EQUIP range of products.



DESIGNED TO PERFORM – MANUFACTURED TO LAST

Key Features :-

- Heavy duty construction,
- Ease of operation,
- Complete with Side Auger and Hopper,
- Complete with internal and external ladders,
- Can be hot dip galvanized.

MIXER MODELS AVAILABLE

MODEL	CAPACITY (M ³)	DIAMETER (METRES)	HEIGHT (METRES)	MOTOR (KW)	NOTES
HM15015V	2.5	1.5	2.33	4	1, 2, 3
HM16512V	3.7	1.65	2.93	4	1, 2, 3
HM18015V	5.1	1.83	3.3	5.5	1, 2, 3
HM19022V	8	2	2.7	7.5	1, 2,
HM19030V	10	2	4.32	11	2
HM19535V	12.8	2	5.48	15	2

Notes:-

1. Available in 240/480 VAC power.
2. Available in 415 VAC power.
3. Can be hot dip galvanized.

SPECIFICATIONS :-

1. Fast and complete mixing, usually within 8 to 15 minutes,
2. Standard range capacities of 2.5 m³ to 12.8 m³ (1.375 tonne to 6.6 tonne),
3. Standard issue complete with LIQUID SUPPLEMENT RING,
4. Easy additive loading with the SIDE AUGER and HOPPER,
5. Simple but effective operation,
6. 3 mm steel in the cone and side walls with 5 mm in the lid,
7. Complete with internal ladder, external ladder and site glass,
8. Pre-configured foot mounts to suit KEOGH'S extensive range of weigh/batching systems,
9. Geared motor drive on SIDE AUGER (no belts or pulleys to wear out),
10. Standard issue taper lock pulleys on main drive,
11. Fitted with standard DUST VENT KIT and bag stand,
12. Designed to be top filled to minimize drive motor power consumption and unit wear,
13. Bottom bearing plate fitted with seal, flinger and triple lip seal in the bottom bearing,
14. Flite assembly straightened to ensure smooth operation,
15. Large diameter central mixing auger,
16. Optional BAGGING CHUTE available,
17. Custom designs available on request,
18. Hot dip galvanized finish available on most models (5.1 m³ and smaller units only),
19. Complete with 1 of OUTLET BOOT for unloading auger (more available on request),

Your nearest dealer in Keogh HAWK-EQUIPMENT is :-



Manufactured in AUSTRALIA by :-

B. KEOGH & SONS MANUFACTURING PTY LTD

Australia's Bulk Commodity Handling Specialists

ACN 006 377 215

York Street, Eaglehawk, Victoria 3556, AUSTRALIA

Telephone 03 54468377 ~ Facsimile 03 54461178

International Phone 613 54468377 ~ International Facsimile 613 54461178

Website www.augers.com.au ~ Email sales@augers.com.au

